Triggers and Active Databases

Chapter 9

1

Trigger Overview

- Element of the database schema
- General form:
  ON <*event*> IF <*condition*> THEN <*action*>
  - *Event*- request to execute database operation
  - *Condition* - predicate evaluated on database state
  - *Action* – execution of procedure that might involve database updates
- Example:
  ON updating maximum course enrollment
  IF number registered > new max enrollment limit
  THEN deregister students using LIFO policy

2

Trigger Details

- **Activation** - Occurrence of the *event*
- **Consideration** - The point, after activation, when *condition* is evaluated
  - Immediate or deferred (when the transaction requests to commit)
  - *Condition* might refer to both the state before and the state after *event* occurs

3

Trigger Details

- **Execution** - point at which *action* occurs
  - With deferred consideration, execution is also deferred
  - With immediate consideration, execution can occur immediately after consideration or it can be deferred
    - If execution is immediate, execution can occur before, after, or instead of triggering event.
    - Before triggers adapt naturally to maintaining integrity constraints: violation results in rejection of event.

4

Trigger Details

- **Granularity** -
  - Row-level granularity: change of a single row is an event (a single UPDATE statement might result in multiple events)
  - Statement-level granularity: events are statements (a single UPDATE statement that changes multiple rows is a single event).

5

Trigger Details

- **Multiple Triggers**
  - How should multiple triggers activated by a single event be handled?
    - Evaluate one condition at a time and if true immediately execute action or
    - Evaluate all conditions, then execute actions
  - The execution of an action can affect the truth of a subsequently evaluated condition so the choice is significant.

6

Triggers in SQL/3

- **Events**: INSERT, DELETE, or UPDATE statements or changes to individual rows caused by these statements
- **Condition**: Anything allowed in a WHERE clause
- **Action**: An individual SQL statement or a program written in the language of Procedural Stored Modules (PSM) (which can contain embedded SQL statements)

7

Triggers in SQL:1999

- **Consideration**: Immediate
  - Condition can refer to both the state of the affected row or table before *and* after the event occurs
- **Execution**: Immediate - can be before or after the execution of triggering event .
  - Action of before trigger cannot modify the database
- **Granularity**: Both row-level and statement-level granularity

8

Before Trigger Example
(row granularity)

```
CREATE TRIGGER  Max EnrollCheck
  BEFORE INSERT ON Transcript
      REFERENCING NEW AS N   --row to be added
  FOR EACH ROW
  WHEN
  ((SELECT  COUNT (T.StudId) FROM Transcript T
     WHERE  T.CrsCode = N.CrsCode
               AND T.Semester = N.Semester)    >=
   (SELECT C.MaxEnroll FROM Course C
     WHERE C.CrsCode = N.CrsCode ))
  ABORT TRANSACTION
```

9

After Trigger Example
(row granularity)

```
CREATE TRIGGER LimitSalaryRaise
  AFTER UPDATE OF Salary ON Employee
  REFERENCING OLD AS O
                NEW AS N
  FOR EACH ROW
  WHEN (N.salary - O.Salary > 0.05 * O.Salary)
     UPDATE Employee          -- action
     SET Salary = 1.05 *  O.Salary
     WHERE Id = O.Id
```

Note: The action itself is a triggering event (but in this case a chain reaction is not possible)

10

After Trigger Example
(statement granularity)

```
CREATE TRIGGER RecordNewAverage
  AFTER UPDATE OF Salary ON Employee
  FOR EACH STATEMENT
    INSERT INTO Log
    VALUES  (CURRENT_DATE,
                SELECT AVG (Salary)
                FROM  Employee)
```

11